

Liquid CLASSIC MARBLE High Gloss Cultured Marble Kit

Turn any paintable surface into an authentic polished marble finish

27 OZ. KIT (COVERS UP TO 12 SQ. FT.)

PLEASE READ ALL INSTRUCTIONS BEFORE BEGINNING PROJECT

WARNING-HARMFUL IF SWALLOWED - If color is swallowed, induce vomiting and CALL A PHYSICIAN IMMEDIATELY. If hardener is swallowed, DO NOT INDUCE VOMITING. Dilute by giving water or milk to drink if victim is conscious. GET MEDICAL ATTENTION IMMEDIATELY. If combined mixture is swallowed, DO NOT INDUCE VOMITING. Dilute by giving water or milk to drink if victim is conscious. GET MEDICAL ATTENTION. **SEVERE EYE IRRITATION** - In case of eye contact, flush with water for ten minutes and seek prompt medical attention. **SKIN** - Color and hardener are skin irritants and may cause allergic reaction. Protective clothing, including plastic gloves, should be worn while handling this compound. If Liquid Marble accidentally comes in contact with skin, wash affected areas with soap and water immediately. **AVOID INHALATION** - Use in well ventilated areas. Color contains epoxy bisphenol, a resin. Hardener contains a polyamine curing agent. Liquid Marble should be used only by adults or under close supervision by an adult. **KEEP OUT OF REACH OF CHILDREN.**

INTRODUCTION

LIQUID MARBLE is an easy one coat process that can turn any paintable surface into an authentic, polished marble look without any top coat. LIQUID MARBLE can be applied to finished or unfinished wood, plastic, metal, pressed board, formica and even glass. This finish is excellent for covering and filling any defects in surfaces, such as deep scratches, nicks or grooves. LIQUID MARBLE will set up in 8 hours and be completely dry to the touch in 24 hours. No top finish is needed to protect the surface. LIQUID MARBLE will attain its maximum hardness after 7 days, and will provide you with a durable, tough finish that is resistant to alcohol, food and drink spills. Simply wipe up spills with soap and water. As each piece of marble is unique, so too will your finished piece of LIQUID MARBLE be as it dries and takes on a beautiful design.

WORK AREA - Work in a dust free room where the temperature is 70-80°. The item that has been coated should be kept in this same room for 24 hours until dry. Do not use fans or other devices that would stir up dust while project is drying. Cooler and humid conditions will slow down initial drying. Store kit at room temperature for 6 hours before using.


INSTRUCTIONS FOR COATING A HORIZONTAL SURFACE

PREPARATION OF PROJECT

1. The surface to be covered must be dry and free of dust, wax, grease or oil. To remove any of these contaminants, wash with T.S.P. or sand lightly. Wipe surface after sanding.
2. Protect the floor beneath your project with newspaper.
3. Surface to be covered must be level.

FOR INTERIOR SURFACES ONLY. DO NOT USE OUTSIDE.

4. Before coating surface with LIQUID MARBLE, apply electricians tape or plastic tape on the underside of the item at the edges. Do not use masking tape. This is to hold any drips which form. After LIQUID MARBLE has dried, the tape along with the drips may be pulled off.



5. Protect the rest of the furniture piece that is not being coated by covering carefully with newspaper using masking tape.


UNFINISHED WOOD OR UNFINISHED PRESSED BOARD - It is necessary to seal these surfaces with white glue or lacquer sanding sealer to prevent air bubbles from escaping into the fluid.

DARK FINISHED SURFACES - It is advisable to spray the surface to be coated with light colored spray paint for ease of coverage if using one of the light shades of LIQUID MARBLE.

IMPORTANT: After mixing color and hardener together, Liquid Marble should not be left in container any longer than mixing instructions indicate, as it will harden in container within 30 to 60 minutes.

MIXING INSTRUCTIONS WHEN USING THE ENTIRE KIT

1. **BASE COLOR** - Into the "Base Color" jar, pour the entire contents of the 8 oz. bottle of "Hardener for Base Color". Using the large 9" stick in your kit, mix briskly for 5 minutes, continuously scraping the sides and bottom of jar, and pulling up material from bottom as you mix. It is important to mix well. Immediately after mixing base color, pour evenly over the surface. (See "Applying Base Coat" on next page.)



2. **Accent Colors** - There are 2 accent colors in your kit. Remove lid from one "Accent Color" jar and into this pour the contents of one bottle marked "Hardener for Accent Colors". Repeat for second accent color. Using small craft sticks in your kit, mix each jar for 2 minutes, scraping the sides and bottom of jar. Set aside for 15 minutes.

B.D. CLASSIC ENTERPRISES, INC.

P.O. Box 2445 SANTA FE SPRINGS, CA 90670

PHONE (562) 944-6177 FAX (562) 946-8572

1-800-543-8551